

THINK CREATE PRINT



PMX 3031ADN

38 PPM.512MB RAM.1GHZ DUAL CORE. DUPLEX.ADF

FOLLOW US



AVAILABLE ON



Toll Free No.

18003099639

info@printmark.net.in

www.printmark.net.in

Contact US



#startupindia

PRINTMARK MONO MULTIFUNCTION PMX 3031adn

Light, Compact, And Fast, The PMX3031dn Multifunction Supports Output Up To 38 Pages Per Minute, Plus Single Pass Duplex Scanning, Copying, & Touch-Screen Convenience. Connect Via USB Or Gigabit Ethernet & Add An Optional 550-Sheet Paper Tray
Available Extra High Yield Toner Offering Up To 20,000 Pages of Output.

	Specification
Print Technology	Laser
Type of Machine	Multifunction Machine
Type of Printing	Mono
Cartridge Technology	Separate Drum and Toner
Paper Size (Original/Image)	A4/A4
Minimum Speed Per Minute as per ISO/IEC 24734 in A4 Size	38 PPM
Print Speed Duplex	34 IPM
Time to First Page Out	6.2 sec
Processor	1 GHz, Dual Core
Memory (RAM)	Standard: 512 MB / Maximum: 512 MB
Display	2.8-inch (7.2 cm) LCD touch panel
USB Port	Yes
Wireless	No
Standard Port	USB 2.0 Specification (Type B), Ethernet 10/100 Base TX (RJ-45)
Network Protocol Support	TCP/IP IPv6, TCP/IP IPv4, TCP, UDP
Resolution	2400 IQ (2400 x 600 dpi), 1200 IQ (1200 x 600 dpi), 1200 x 1200 dpi, 600 x 600 dpi (default), 300 x 300 dpi
Duty Cycle (No of Prints/month)	50000 pages
Number of Main Paper Tray	1
Each Main Paper Tray Capacity	250 Sheets
Bypass Tray Capacity	100 Sheets
Paper Output Capacity	150
Document Feeder Type	ADF-50 Sheets
Media Size supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Aficio, A6
Media Type	Paper Labels, Card Stock, Plain Paper, Envelopes
Duplexing Feature Availability	Yes
Platen/Flatbed Size	A4
Scanner Type / ADF Scan	Flatbed scanner with ADF / Simplex
Colour Scanning	Yes
Scan Format	TIFF, PDF, JPEG, JPG
Reduction/Enlarge Range	25 ~ 400%
Scan Destination	E-mail, USB, Network, Connected computer FTP
Network Scanning	Yes
Yield of the cartridge supplied with Machine as per ISO/IEC: 19752/2004(E)	1500 pages
After market Cartridge Capacity	1500, 6000 & 20000 pages
Imaging Unit Capacity	40000 pages
Print Language	PCL5e Emulation, PCL 5e Emulation, PCLm, PCL6 Emulation, Direct Image
OS Support *	Windows 7 and above, SUSE Linux 12 and above, Ubuntu 16.04 and above, Red Hat Enterprise Linux WS 6.10 and above
Certification	BIS, ROHS, CE, BEE, NABL Approved
Noise Level	Print: 53 dBA / Copy: 54 dBA / Scan: 55 dBA
Size/Weight	H x W x D: 339 x 411 x 366 mm / 12.8 kg
Warranty	1 Year Onsite Support

All information in this brochure is subject to change without notice. Printmark is not liable for any errors or omissions.

1- Average standard page yield value declared in accordance with ISO/IEC 19752. 2-" Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Printmark's product offerings based on the average number of pages customers plan to print on the device each month. Printmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals, paper loading intervals, speed, and typical customer usage. 3-" Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Printmark printers and MFPs. 4-Printers are sold subject to certain license/agreement conditions. 5-Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. 6-Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively.

*For Detailed OS Support Please visit our website www.printmark.net.in

© 2024 Printmark. All rights reserved. Printmark, the Printmark logo are trademarks of Printmark Technologies Pvt Ltd, registered in India.